## TECHNICAL DATA/SPECIFICATION

MODEL: SRE-3050 ELAN STRAIGHT RAIL STAIRLIFT, PRIVATE RESIDENCE ONLY

RATED LOAD: 300 LBS, ONE PASSENGER

POWER SOURCE: 24 VOLT DC COMPRISED OF (2) 3 AMP/HR

12 VOLT SEALED BATTERIES

105-230 VOLT AC 0.6 AMP, 24 VOLT DC 1 AMP

CONTINUOUS MONITORING CHARGER.

DRIVE: 24 VOLT DC DIRECT DRIVE SELF LOCKING POSITIVE GEARED MOTOR,

2 POLE RATED .18 HP MAX., RIGHT ANGLE WORM GEARBOX,

50Nm (442in.lb.) TORQUE MAX., 25.5 RPM SPEED MAX.,

16 AMP CURRENT MAX.

SUSPENSION: RACK & PINION - INTEGRATED 8DP GEAR RACK ON RAIL WITH SPUR GEAR ON THE OUTPUT SHAFT

OF GEARBOX.

BRAKING: DYNAMIC MOTOR BRAKING THROUGH THE MOTOR

CONTROLLER, WORM GEAR, ELECTRO-MECHANICAL

MOTOR BRAKE AND OVERSPEED PROTECTION.

CONTROLS: CONTINUOUS PRESSURE ROCKER SWITCH LOCATED

ON THE ARMREST AND WALL MOUNTED CALL/SEND


CONTROLS LOCATED AT BOTH THE TOP AND BOTTOM

LANDINGS.

ANGLES: 22 TO 45 DEGREES (SPECIALS UP TO 52 DEGREES),

RIGHT OR LEFT HAND ORIENTATIONS.


FINAL LIMIT SWITCH: STANDARD




## SIDE VIEWS

ILS-01459 SHEET 1 OF 3 REV. 1 (7259)(8/4/2020)(BHM)


DIMENSIONS SHOWN IN SIDE VIEWS ARE BASED ON 4-1/2" RAIL POSITION FROM WALL OR OBSTRUCTION



## SRE-3050 DISTANCE FROM WALL - SEAT SWIVELED




SEAT SWIVELED 67°




SEAT SWIVELED 90°

1780 Executive Drive Oconomowoc, WI 53066 www.bruno.com





## SRE-3050 FOLDING RAIL



ILS-01459 Folding Rail SHEET 3 OF 3 REV. 1 (7259)(8/4/2020)(BHM)

